PRODUCT INFORMATION

HUSKEY[™] ENCLOSED GEAR OILS

DESCRIPTION

HUSKEY GEAR OILS are all-purpose, extreme pressure gear oils formulated from the highest quality selected base oils and additives available. **HUSKEY GEAR OILS** have been compounded to be more reliable, even under the toughest conditions. These high-quality oils have been formulated to give extra protection in high-temperature applications. Special polymer additives track on all gear teeth, coating the metal surfaces to reduce backlash and quiet worn or noisy gears. **HUSKEY GEAR OILS** meet or exceed most *major specifications and perform to almost all equipment requirements.

USAGE

HUSKEY GEAR OILS outstanding quality is the versatility of their applications, which include almost all worm, spur, herringbone, and planetary gears. They are designed primarily for industrial gear applications but are excellent for automotive uses such as manual transmissions, differentials, steering boxes, etc.

ADVANTAGES

- Suited for Different Applications
- Excellent Load-Carrying Capacity
- Reduces Wear and Protects Against Scuffing. Increases Gear Life
 - * Meets API GL-4, and GL-5 requirements
 - * Meets Mil-L-2105C requirements
- Protects Against Rust, Corrosion and Foaming
- Helps Quiet Worn and Noisy Gears
- * Meets U.S. Steel Specification 224
- * Meets AGMA 250.03 requirements

PACKAGE AVAILABILITY

Convenient 1 gal. jugs (4 jugs per case) 5 gal. Pails, 15 gal. Kegs and 55 gal. Drums



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office: 1580 Industrial Avenue, Norco, California 92860 (951) 340-4000 · Fax: (951) 340-4011 (888) 4-HUSKEY · www.huskey.com

Eastern Region Office: 8300 Corporate Park Drive, Macedonia, Ohio 44056 (330) 425-2567 · Fax: (330) 425-9637 (800) 238-LUBE

* PRODUCT INFORMATION

TYPICAL SPECIFICATIONS

DESCRIPTION: HUSKEY Product: Enclosed Gear Oil

Color: Brown
Base Oil: Petroleum

<u>TEST</u>	ASTM METHOD	<u>90wt</u> Gear Oil	<u>140 wt</u> <u>Gear Oil</u>	85 W-140 Gear Oil
Base Oil Viscosity, SUS @ 100°F SUS @ 210°F	D-445 D-445	1195 99	2590 155	2101 137
Viscosity Index, min.	D-2270	98	96	97
Gravity, API		22.4	21.3	33.6
Pour Point, °F	D-97	0	-3	-4
Flash Point, °F	D-92	470	518	500
Rust Test	D-665	PASS	PASS	PASS
Timken OK Load, lbs	. D-2509	70	70	70
Oxidation Test	D-943	PASS	PASS	PASS
ISO Grade		220	460	

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

1/04



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office: 1580 Industrial Avenue, Norco, California 92860 (951) 340-4000 · Fax: (951) 340-4011 (888) 4-HUSKEY · www.huskey.com Eastern Region Office: 8300 Corporate Park Drive, Macedonia, Ohio 44056 (330) 425-2567 • Fax: (330) 425-9637 (800) 238-LUBE