* PRODUCT INFORMATION :

HUSKEY[™] HTL-500 ULTRA -LOW GREASE

DESCRIPTION

HUSKEY HTL-500 ULTRA LOW GREASE represents some of the most advanced lubricant technology. It is a versatile, premium quality, synthetic grease fortified with PTFE. Blended completely from pure synthetic base oils, additives and shear stable thickeners to provide maximum equipment protection in extremely low and high temperatures (Operating Range -100° to 430°F). **HUSKEY** HTL-500 ULTRA LOW GREASE is also NSF/U.S.D.A. H-1 registered and KOSHER approved, which gives it full acceptability for use in all areas where incidental food contact may occur.

USAGE

HUSKEY HTL-500 ULTRA LOW GREASE is truly a multi-service lubricant for extended service under extreme low and high conditions. **HUSKEY** HTL-500 ULTRA LOW GREASE has proven to be a problem solving product in a wide variety of industries and applications. Some such applications include: Freezer Door Hinges and Bearings, Oven Bearings and Chains, Pumps, Kilns, Conveyors, etc.

ADVANTAGES

- NSF/USDA H-1 REGISTERED
- WATER AND STEAM RESISTANT
- NON-MELTING

- NON-STAINING
- WIDE TEMPERATURE RANGE
- REDUCES FRICTION AND WEAR

TYPICAL RESULTS

Base Type	Synthetic	Base Oil Viscosity,	
N.L.G.I. No.	2	SUS @ 100°F	91
Worked Penetration	285	SUS @ 210°F	39
Dropping Point, °F	None	cSt @ 40 °C	17
Color	Translucent White	cSt @ 100 °C	3.9
Timken OK Load, lbs.	35	Solid Lubricant	PTFE
Flash Point, °F	430	Pour Point, °F	-100

PACKAGE AVAILABILITY



5 gal. Pails,15 gal. Kegs, and 55 gal. Drums

NSF Registrtaion No. 059313



The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.



HUSKEY Specialty Lubricants

manujacored by HUSK ITT Corporation - SPECIALTY LUBRICANTS Corporation Western Region Office: Eastern Region Office: Eastern Region Office: 2057 Exst Autora Road (209) 340-4000 Face (209) 340-4011 (330) 425-2567 Face (2000) structure Region Office: (2000) 540-4011 (2000) Face (2000) 540-4011 (2000) 540-40

Eastern Region Office: 2057 Et st Aurora Road, Transburg, Ohio 44087 (330) 425-2567, Fax: (330) 425-9637