

APPLICATION CHART FOR *HUSKEY*™ GREASES

Codes:

E= Excellent

F=Fair

WP=Waterproof

VG= Very Good

WR=Water Resistant

G= Good

NR=Not Recommended

Table 1

INDUSTRIAL GREASES	COOLPLEX	MOLY-GRAPH	COOLUBE	COOLUBE 65	TF-1000	TUFF STUFF	105 HI-TEMP	DYNA-MITE RED	MOLYPLEX	HTS-2
Product Code	200	300	100	1300	400	1400	500	600	800	1100
Color	AMBER	BLACK	GREEN	AMBER	CREAM	BROWN	BROWN	RED	MOLY GRAY	MOLY GRAY
Base Oil	MINERAL OIL	MINERAL OIL	MINERAL OIL	MINERAL OIL	SEMI-SYNTHETIC	MINERAL OIL	MINERAL OIL	SEMI-SYNTHETIC	SEMI-SYNTHETIC	SYNTHETIC
Thickener	SYNTHETIC	SYNTHETIC	SYNTHETIC	CA 12 HYDRO STEARATE	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC
Solid Lubricants		MOLY AND GRAPHITE			PTFE				MOLY, "WHITE MOLY"	MOLY
Base Oil Viscosity, CST at 40 °C	144	109	58	15	135	225	473	677	595	87
Dropping Point, °C	NONE	NONE	NONE	149	NONE	NONE	NONE	NONE	NONE	NONE
Service Temperature, °C (°F)	-14 TO 285 (7 TO 545)	-15 TO 274 (5 TO 525)	-40 TO 204 (-40 TO 440)	-54 TO 49 (-65 TO 300)	-15 TO 274 (5 TO 525)	-29 TO 282 (-20 TO 540)	-12 TO 308 (10 TO 586)	-12 TO 274 (10 TO 525)	-12 TO 241 (10 TO 465)	-37 TO 260 (-35 TO 500)
Presence of Water	WR	WR	WR	WP	WP	WR	WR	WP	WP	WR
Harsh Chemicals	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR
Cost	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$ \$
Heavy Loads	G	E	G	E	G	E	E	E	E	E
Journal Bearings-										
Low Speed	G	G	F	F	G	E	E	E	E	F
Medium Speed	E	E	G	G	E	G	G	G	G	G
High Speed	G	G	E	E	G	NR	F	F-G	F	E
Ball and Roller Bearings-										
Low Speed	G	G	G	G	E	E	E	E	E	F
Medium Speed	E	E	G	G	E	G	G	G	G	VG
High Speed	G	G	E	E	G	F	G	G	F	E
Additional Properties	MP, T	MP, T	MP		MP, T	MP, T	MP	T	MP, FWP, T	MP
Containers	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum

1. The information in this chart is meant to be informative. The potential consumer should test the greases before use.

FOOD GRADE GREASES (NSF/USDA H-1 Registered for Incidental Food Contact)

FOOD GRADE GREASES	775 FMG	LUBE "O" SEAL	LVI-50	HTL-500	HTL-500 ULTRA LOW	HYDROLUBE	HVS-100	350 SILICONE	PF-27	PF-30	ECO-LUBE EP 2
Product Code	77500	00900	01000	73100	72700	87800	76700	35000	78200	77100	58500
Color	WHITE	TRANSLUCENT WHITE	TRANSLUCENT WHITE	TRANSLUCENT WHITE	TRANSLUCENT WHITE	WHITE	TRANSLUCENT WHITE	TRANSLUCENT WHITE	WHITE	WHITE	AMBER
Base Oil	SEMI-SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SILICONE	SILICONE	PFPE	PFPE	VEGETABLE
Thickener	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	SYNTHETIC	PTFE	PTFE	SYNTHETIC
Solid Lubricants		PTFE	PTFE	PTFE	PTFE	"WHITE MOLY"			PTFE	PTFE	PTFE
Base Oil Viscosity, CST at 40 °C	156	7800	781	47	17	7800	NOT DETERMINED	NOT DETERMINED	450	140	35.8
Dropping Point, °C	NONE	NONE	NONE	NONE	NONE	+260	NONE	NONE	NONE	NONE	NONE
Service Temperature °C (°F)	-12 TO 204 (10 TO 400)	-7 TO 177 (20 TO 350)	-24 TO 163 (-10 TO 325)	-59 TO 266 (-75 TO 510)	-68 TO 215 (-90 TO 420)	-7 TO 63 (20 TO 350)	-46 TO 299 (-50 TO 570)	-48 TO 299 (-55 TO 570)	-25 TO 302 (-13 TO 575)	-40 TO 302 (-40 TO 575)	-29 TO 271 (-20 TO 520)
Presence of Water	WR	WP	WP	WR	WR	WP	WP	WP	WP	WP	WR
Harsh Chemicals	G	G	G	G	F	G	G	G	E	E	G
Cost	\$ \$	\$ \$	\$ \$	\$ \$	\$ \$	\$ \$	\$ \$ \$	\$ \$ \$	\$ \$ \$ \$	\$ \$ \$ \$	\$ \$
Heavy Loads	G	E	E	G	G	E	F	NR	E	G-E	VG
Journal Bearings-											
Low Speed	G	E	G	G	G	E	G	NR	E	G	G
Medium Speed	G	G	G	G	G	G	F	F	G	E	VG
High Speed	E	NR	G	E	E	NR	NR	G	NR	E	VG
Roller/Ball Bearings-											
Low Speed	G	E	E	G	G	E	G	NR	E	G	G
Medium Speed	G - E	G - NR	G	E	E	G - NR	F	F	E	E	VG
High Speed	E	NR	G	E	E	NR	NR	G	G	E	VG
Additional Properties	MP, T	T, D	MP, T, D	MP, D	MP, D	FWP, T	T, D	D, T	NFP, MP, LGL, FWP, AS	NFP, MP, LGL, FWP, AS	MP
Containers	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	Cartridge, 1 & 5 gal. pails, 15 gal. keg and 55 gal. drum.	3 gram pack, Cartridge, 1 & 5 gal. pails, 15 gal. keg and 55 gallon drum.	Cartridge, 1 & 5 gal. pails, 15 gal. keg and 55 gal. drum.	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum	1 & 5 gal. pails, 15 gal. keg and 55 gal. drum.	3 gram pack, 3 oz. tube, 1 & 5 gal. pails, 15 gal. keg and 55 gal. drum.	1 & 5 gal. pails, 15 gal. keg and 55 gal. drum.	1 & 2 oz. 16 oz (1/2 Pint), 1-1/2 lb. Jar and Cartridge, 16 lb (1 gal.), 55 lb. (5 gal. pail)	1 & 2 oz. 16 oz (1/2 Pint), 11/2 lb. Jar and Cartridge, 16 lb (1 gal.), 55 lb (5 gal. pail)	Cartridge, 1 & 5 gal pails, 15 gal. keg and 55 gal. drum

1. HUSKEY greases are standard NLGI 2 consistency with the exceptions of HVS-100, 220-R and 350 Silicone, which are NLGI 3 consistency.

2. Greases with NLGI 00, 0, or 1 are available upon request. However, we do not offer these grades in cartridges.

Printed in USA Rev.1/11